

## High Temperature Medium Duty Castors and Wheels

### 34 (Pressed Steel Bracket) and GNG Series (Fabricated Bracket)

Pressed or fabricated steel brackets, specialist wheels and double ball race swivel heads make these ranges suitable for use in more extreme internal and external applications. Rated to temperatures of -40 C to +280 C.



GNG Series Frames and wheels are supplied GREASE FREE with grease nipples for the user to apply the appropriately rated high temperature grease. Temperature ratings will then be dependent upon the specific grease used.

Wheel Dia. (mm)	Tread Width (mm)	Load Cap. (kg)	Overall Height (mm)	Plate / Bolt Hole Dimensions (mm)		Suits Bolt Dia. (mm)	Wheel Type	Bearing Type	Swivel Radius (mm)	Catalogue Reference		
				Plate	Bolt Ctrs					Swivel	Swivel Braked	Fixed
<b>34 Series Top Plate Fitting</b>												
80	35	100	108	Swivel 105 x 85 Fixed 103 x 85	80/77 x 60	9	Phenolic Resin	Plain	84.5	3470BOC080P62	3477BOC080P62	3478BOC080P62
100	35	125	128	Swivel 105 x 85 Fixed 103 x 85	80/77 x 60	9	Phenolic Resin	Plain	91	3470BOC100P62	3477BOC100P62	3478BOC100P62
125	35	150	155	Swivel 105 x 85 Fixed 103 x 85	80/77 x 60	9	Phenolic Resin	Plain	102.5	3470BOC125P62	3477BOC125P62	3478BOC125P62
160	50	250	200	Swivel 137 x 105 Fixed 137 x 115	105 x 80	11	Phenolic Resin	Plain	135	3470BOC160P63	3477BOC160P63	3478BOC160P63
200	50	300	240	Swivel 137 x 105 Fixed 137 x 115	105 x 80	11	Phenolic Resin	Plain	135	3470BOC200P63	3477BOC200P63	3478BOC200P63
<b>34 Series Bolt Hole Fitting</b>												
80	35	100	108	-	-	13	Phenolic Resin	Plain	84.5	3470BOC080P30	3477BOC080P30	n/a
100	35	150	128	-	-	13	Phenolic Resin	Plain	91	3470BOC100P30	3477BOC100P30	n/a
125	40	200	155	-	-	13	Phenolic Resin	Plain	102.5	3470BOC125P30	3477BOC125P30	n/a
<b>GNG Series Top Plate Fitting (Fabricated Bracket)</b>												
100	45	320	142	130 X 105	105 x 80/75	10	Cast Iron	Plain	89	TSG100CI0GNG	n/a	TFG100CI0GNG
150	45	450	189	130 X 105	105 x 80/75	10	Cast Iron	Plain	124	TSG150CI0GNG	n/a	TFG150CI0GNG

### BOO Series High Temperature Wheels

Phenolic Resin wheels with a Plain bore. temperature rated from -40 C to +280 C.



Wheel Dia. (mm)	Tread Width (mm)	Bore Size (mm)	Hub Length (mm)	Load Cap. (kg)	Bearing Type	Catalogue Reference
80	35	12.2	40	100	Plain	8000803512
100	35	12.2	40	125	Plain	8001003512
125	35	12.2	40	150	Plain	8001253512
160	50	20.2	58	250	Plain	8001605020
200	50	20.2	58	300	Plain	8002005020