

Pneumatic and Solid Rubber Tyred Wheels

PW, BW, Centaure and NSS Series Wheels

A range of rugged pneumatic and solid tyred wheels.

Pneumatic Tyred Wheels



PW Series
Pneumatic 4Ply tyre
with Polypropylene
centre.

Wheel Dia		Tread Width (mm)	Bore Size (mm)	Hub Length (mm)	Load Cap. (mm)	Bearing Type	Catalogue Reference
Inches	(mm)						
8.75	220	65	25.4	75	100	Plain	PW250-425.4/754/51R
8.75	220	65	25.4	75	100	Roller	PWR250-425.4/754/51R
10.5	260	82	25.4	75	120	Plain	PW300-425.4/754/52R
10.5	260	85	25.4	75	120	Roller	PWR300-425.4/754/52B
12	300	100	25.4	75	150	Roller	PWR400-425.4/754/52R

BW Series
Pneumatic 4Ply tyre
with black or red
metal centre.



Wheel Dia		Tread Width (mm)	Bore Size (mm)	Hub Length (mm)	Load Cap. (kg)	Bearing Type	Catalogue Reference
Inches	(mm)						
8.75	220	65	25.4	66	100	Roller	BWR250-425.4/664/51R
10.5	260	85	25.4	66	170	Plain	BWG300-425.4/664/52R
10.5	260	85	25.4	66	170	Roller	BWR300-425.4/664/52R
12	300	100	25.4	66	245	Roller	BWR400-425.4/664/52B
16	400	100	25.4	63	305	Roller	BWR400-825.4/634/01B
16	400	100	25.4	83	305	Ball Journal	BWB400-825.4/834/01B

Solid Tyred Wheels



Centaure Series
Black solid rubber
tyre with a Silver
metal centre.

Wheel Dia		Tread Width (mm)	Bore Size (mm)	Hub Length (mm)	Load Cap. (kg)	Bearing Type	Catalogue Reference
Inches	(mm)						
6	160	40	25.4	51	175	Plain	744 162 2600
6	160	40	25.4	51	175	Roller	745 162 2600
7	180	50	25.4	51	200	Plain	744 180 2600
7	180	50	25.4	51	200	Roller	745 180 2600
8	200	50	25.4	51	250	Plain	744 200 2600
8	200	50	25.4	51	250	Roller	745 200 2600
10	250	50	25.4	51	350	Plain	734 250 2600
10	250	50	25.4	51	350	Roller	735 250 2600
12	300	50	25.4	51	400	Plain	734 300 2600
12	300	50	25.4	51	400	Roller	735 300 2600

NSS Series
Black solid rubber
tyre with a black
metal centre.



Wheel Dia		Tread Width (mm)	Bore Size (mm)	Hub Length (mm)	Load Cap. (mm)	Bearing Type	Catalogue Reference
Inches	(mm)						
8	200	50	25.4	51	250	Plain	NSS 200 25.4/51BLK
8	200	50	25.4	51	250	Roller	NSS 200 R25.4/51BLK
10	250	50	25.4	51	350	Plain	NSS 250 25.4/51BLK
10	250	50	25.4	51	350	Roller	NSS 250 R25.4/51BLK

Wheels

WAT, WRT & WAN Series

A range of rubber tyred wheels suitable for a wide range of uses.



WAT Series Heavy Duty

Pneumatic rubber tyre, zinc plated steel disc centre.

Wheel Dia. (mm)	Tread Width (mm)	Bore Size (mm)	Hub Length (mm)	Load Cap. (kg)	Bearing Type	Catalogue Reference	USED IN CASTOR SERIES
Black Tyre							
196	48	20	60	75	Roller	WAT8RBW20	22
Grey Tyre							
196	48	20	60	75	Roller	WAT8RBW20	22

WRT Series Heavy Duty

Black rubber tyre, black cast iron centre.

NB. Ball journal bearings are available in a selection of bore sizes in 150mm, 200mm and 250mm sized wheels - call for details.



Wheel Dia. (mm)	Tread Width (mm)	Bore Size (mm)	Hub Length (mm)	Load Cap. (kg)	Bearing Type	Catalogue Reference	USED IN CASTOR SERIES
100	43	15	48	160	Roller	WRT4RBW15	SL, 61, 22
125	38	15	48	180	Plain	WRT5W15	SL, 61, 22
125	38	15	48	180	Roller	WRT5RBW15	SL, 61, 22
150	45	20	60	400	Plain	WRT6W20	KV, GT, SL, JA, 61, 55
150	45	20	60	400	Roller	WRT6RBW20	KV, GT, SL, JA, 61, 55
150	45	25	60	400	Roller	WRT6RBW25	-
150	45	25.4	60	400	Plain	WRT6L	-
150	45	25.4	60	400	Roller	WRT6LRB	-
200	51	20	60	585	Plain	WRT8W20	KV, GT, SL, JA, 61, 55
200	51	20	60	585	Roller	WRT8RBW20	KV, GT, SL, JA, 61, 55
200	51	25	60	585	Roller	WRT8RBW25	-
200	51	25.4	60	585	Plain	WRT8L	-
200	51	25.4	60	585	Plain	WRT8LRB	-
250	51	25	60	680	Roller	WRT10RBW25	KV, GT
250	51	25.4	60	680	Roller	WRT10RB	-
250	51	31.8	60	680	Roller	WRT10LRB	-
300	57	25	60	750	Roller	WRT12RBW25	KV
300	57	25.4	60	750	Roller	WRT12RB	-
300	57	31.8	60	750	Roller	WRT12LRB	-
300	102	31.8	118	2000	Taper	WRT312TM40	EH



WAN Series Heavy Duty

Black reinforced Phenolic resin wheel.

Wheel Dia. (mm)	Tread Width (mm)	Bore Size (mm)	Hub Length (mm)	Load Cap. (kg)	Bearing Type	Catalogue Reference	USED IN CASTOR SERIES
75	38	12	41	150	Plain	WAN3M12	61
100	38	15	41	305	Plain	WAN4M15	61, 22
100	38	14.3	41	305	Roller	WAN4RB	61, 22
125	38	15	41	395	Plain	WAN5M15	61, 22
125	38	19.1	56	395	Roller	WAN5RB	61, 22
150	51	19.1	56	540	Roller	WAN6RB	55, 61, KV
200	51	19.1	56	725	Roller	WAN8RB	55, KV, GT