

Pneumatic and Puncture Proof Castors and Wheels

PNB Series & Puncture Proof Range

Two ranges of rugged castors and wheels suitable for a variety of more demanding external applications.

PNB Series Pneumatic Castors



Wheel Dia. (mm)	Tread Width (mm)	Load Cap. (kg)	Overall Height (mm)	Top Plate Dimensions		Bolt Ctrs	Wheel Type	Bearing Type	Swivel Radius (mm)	Catalogue Reference		
				Plate	Bolt Ctrs					Swivel	Braked	Fixed
200	50	75	240	S137 x 105 F137 x 115	105 x 80	10	Pneumatic Rubber Tyre (Rib Tread Black)	Roller	155	KS200PNB	KS200PNB8R	KF200PNB
260	85	150	302	S200 x 160 F200 x 160	150 x 115	14	Pneumatic Rubber Tyre (Diamond Tread Black)	Roller	215	KS260APNB	KS260APNB8R	KF260APNB
260	85	150	302	S200 x 160 F200 x 160	150 x 115	14	Pneumatic Rubber Tyre (Diamond Tread Grey)	Roller	215	KS260APWRRIB	KS260APWRRIB8R	KF260APWRRIB

Puncture Proof Castors



Wheel Dia. (mm)	Tread Width (mm)	Load Cap. (kg)	Overall Height (kg)	Top Plate Dimensions		Bolt Ctrs	Wheel Type	Bearing Type	Swivel Radius (mm)	Catalogue Reference		
				Plate	Plate					Swivel	Braked	Fixed
200	50	100	240	S137 x 105 F135 x 115	105 x 80	10	Puncture Proof Tyre	Roller	155	KS200EVA	KS200EVA8R	KF200EVA
240	85	150	297	S200 x 160 F200 x 160	150 x 115	14	Puncture Proof Tyre	Roller	210	KS260EVA	KS260EVA8R	KF260EVA

Replacement wheels to suit above castors



Wheel Dia. (mm)	Tread Width (mm)	Bore Size (mm)	Hub Length (mm)	Load Cap. (kg)	Bearing Type	Tyre Colour / Tread Pattern	Catalogue Reference
Pneumatic Wheels							
200	50	20	60	75	Roller	Black / Rib	AW200PNB
260	85	20	88	150	Roller	Black / Diamond	AW260PNB
260	85	20	75	150	Roller	Grey / Rib	26220R
Puncture Proof Wheels							
200	50	20	60	100	Roller	Black / Rib	EVA200R20/60BLACK
240	85	20	75	150	Roller	Black / Rib	PWR260PUNCTUREPROOF